

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau




(43) International Publication Date
26 September 2002 (26.09.2002)

PCT

(10) International Publication Number
WO 02/074612 A1

- (51) International Patent Classification⁷: **B62D 65/02**, F16B 5/06
- (21) International Application Number: PCT/AU02/00322
- (22) International Filing Date: 20 March 2002 (20.03.2002)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
PR 3851 20 March 2001 (20.03.2001) AU
- (71) Applicant (*for all designated States except US*):
TELEZYGOLOGY [AU/AU]; Suite 1101, 61 Lavender Street, Milsons Point, NSW 2061 (AU).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- (72) Inventor; and
- (75) Inventor/Applicant (*for US only*): **RUDDUCK, Dickory** [AU/AU]; 81 Castle Circuit, Seaforth, NSW 2092 (AU).
- (74) Agent: **CHRYSILIOU, Kerry**; Chrysiliou Law, CMC Centre, 143 Sydney Road, Fairlight, NSW 2094 (AU).
- Published:**
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: INTERNAL JIGGING



(57) Abstract: A jigging device, for example, for positioning parts to facilitate assembly line procedures. The jigging device maintains a first element (10) in a desired spatial relationship with a second element (12). The jigging device has a first fastening means comprising fastener (20) which is connected to the first element (10). The jigging device also has a second fastening means comprising fastener insert (14) together with adjustable capsule (18). Locking pin (22) locks fastener (20) to the adjustable capsule (18).

WO 02/074612 A1

Internal Jigging

Technical Field

This invention relates to jigs and jigging devices. In particular this invention relates
5 to jigging devices which may be regarded as internal and permanent compared to known jigging arrangements.

The invention also relates to a novel method of jigging.

Background Art

Jigs and jigging devices are generally well known and widely used in manufacture.
10 Typically, a jig will have various reference surfaces and/or points to permit accurate alignment of parts or tools. It is common to jig parts during many manufacturing processes, so that the parts are held in correct juxtaposition during such processes as punching, riveting, welding, gluing or curing. Jigs are regarded as an essential part of the manufacturing process and represent a significant part of
15 the cost of manufacture as well as demanding logistical consideration during production.

1 Most jigging processes are carried out using jigs which are external to the object being formed. Such prior art jigging processes often require clamps, temporary braces or profiles of the final form of the object.

20 Some of the problems presented by prior art jigging can be described, by way of example, in connection with the manufacture of steel-framed vehicles. In the manufacture of such vehicles, in this example the frame is tubular and panels for the vehicle are glued to the frame. During the adhesion process, it is necessary to adjust one panel relative to another and to hold the panels in the correct position
25 while the adhesive cures. In the past, this has been achieved by the use of external clamps, etc. There are drawbacks with the use of clamps, however. For example, clamps must be carefully removed and returned to the panel assembly station, complicating production line issues. Often, damage is caused to the panels due to the pressure required to hold the parts together. Clamps do not contribute to the
30 final assembly strength. In addition, their presence precludes painting and access to other production line issues, such as cabling.

In many instances, it is not possible to progress the vehicle along an assembly line until the adhesive has cured. This results in inefficiency in the manufacturing process, with a costly time delay and/or the need for multiple adhesive stations.

Disclosure of the Invention

- 5 It is an aim of the present invention to provide a jigging device and a method of jigging which, at least in some embodiments, can allow parts to be positioned using internal, not external, means. It is a further aim of this invention, in some embodiments, to enable automated and programmed tolerance control during the pre-assembly process. It is a further aim to provide jigging which need not be
10 removed, so that assembly line procedures can continue uninterrupted.

Accordingly, this invention provides a jigging device for maintaining a first element in spatial relationship to a second element, the device including a first fastening means for connection to the first element and a second fastening means for connection to the second element, at least one of the first and second fastening
15 means including adjustment means for adjusting the spatial relationship between the first and second elements, the device also including locking means adapted to lock the first fastening means to the second fastening means.

The invention also includes a jigging method for maintaining a first element in spatial relationship to a second element, the method including the steps of:

- 20 (1) connecting a first fastening means to the first element;
(2) connecting a second fastening means to the second element;
(3) adjusting the spatial relationship of the first element to the second element via adjustment means; and
(4) locking the first fastening means to the second fastening means.
- 25 Preferably, step (4) is followed by step (5) in which the first element is connected to the second element via adhesion, welding or a similar manufacturing process.

It is to be understood that in the jigging method of the invention, the steps can be carried out in an order different from that set out above. By way of example, step (2) can be carried out after step (3).

- 30 The first element and the second element can be chosen from a wide variety of options. By way of example, in the manufacture of framed vehicles, the first

element may be part of a tubular frame for the vehicle, while the second element may be a panel. Using the jiggling device or method of the invention, the panel may be adjusted in any desired spatial relationship to the frame. For example, the panel may be adjusted to be closer to or further away from the frame. The panel may be
5 adjusted so as to be closer to or further away from an adjacent panel.

The first and second fastening means and the adjustment means may similarly be chosen from a wide variety of options, as can the locking means. While it is to be understood that the first and second fastening means, the adjustment means and/or the locking means may be manipulated manually or presented in a relatively
10 unsophisticated form, it is preferred that the locking means, at least, can be activated, to be locked or unlocked, remotely. In this regard, the contents of international patent application No. PCT/AU99/00185 are imported herein by reference. This specification discloses various forms of locking means and remote activation for such locking means and adjustment means.

15 It is an option with the jiggling device and method of the invention that the adjustment means may be associated more with one fastening means than the other. It is a further option that a first adjustment means is associated with the first fastening means and a second adjustment means is associated with the second fastening means, enhancing the ways in which the spatial relationship can be
20 changed.

Using the jiggling device and method of the invention, it is possible to adjust one element such as a panel in an exact spatial relationship with a second element such as a steel frame, release the first element from the second element and relocate the same panel or a substitute panel (if the first panel is damaged) in the exactly
25 required location on the frame. Further, it is possible, after the respective elements have been located in the correct position, to remove one of the elements, apply adhesive and replace that element, once again in the exact required location. In this embodiment, the jiggling device of the invention will hold the first element in the correct location with respect to the second element while the adhesive cures.

30 The fastening means may be connected to the element in any desired way, including by using adhesive, by using a collar into which the fastening means can be fitted, by using double-sided tape (of suitable peel strength), by otherwise attaching the first fastening means to the element, or by moulding or forming the fastening means in or on the element.

The adjustment means may provide adjustment in any desired manner. By way of example, the adjustment means may have a series of serrations or a screw thread, in each case adapted to be received in a complementary shape. By way of further example, the adjustment means may have first and second parts, one being able to
5 slide into the other to permit adjustment.

While the jiggling device of the invention can incorporate locking means working along the same principle as the fastening and release systems of international patent application No. PCT/AU99/00185, it is a further option that the jiggling device of the invention may be "intelligent" - namely, the jiggling device may possess means
10 which enables automated adjustment of the first element relative to the second element. By way of example, the intelligent means may be capable of sensing an undesirable gap between adjacent panels and of automatically activating the adjustment means to close the gap so that it falls within a preset tolerance. In this way, panels, etc, can become self-adjusting.

15 It is also to be understood that the jiggling device and method of the invention can be used in different ways. The jiggling device can be used to temporarily fasten one element to another, while enabling the accurate positioning of the elements. Once the correct position of the elements has been achieved, one element can be locked to the other by use of the jiggling device of the invention. Optionally, the jiggling
20 device can permit disassembly of the elements while potentially maintaining the correct setting. On this basis, when the elements are assembled again, they immediately are located in the correct, predetermined, relative position.

Brief Description of the Drawings

The invention will now be described in relation to certain non-limiting
25 embodiments illustrated in the attached drawings, in which:

Figures 1 to 3 illustrate, in cross-sectional view, a first embodiment of the jiggling device and method of the invention;

Figures 4 to 9 illustrate in more detail and in magnified view some of the parts of the embodiment shown in Figures 1 to 3;

30 Figures 10 to 13 illustrate in cross-sectional view a second embodiment of the jiggling device and method of the invention;

Figure 14 is a magnified view of the second embodiment;

Figures 15 and 16 show the second embodiment in longitudinal cross-sectional view;

Figure 17 is a top view of the second embodiment;

Figure 18 is a side elevation of the second embodiment;

- 5 Figures 19 to 22 show in cross-sectional view a third embodiment of the jiggling device and method of the invention;

Figure 23 is a close-up view of Figure 21;

Figure 24 is a magnified view of the third embodiment;

Figures 25 and 26 show the third embodiment in longitudinal cross-sectional view;

- 10 Figure 27 shows a top view of the third embodiment; and

Figure 28 shows a side elevation of the third embodiment.

Detailed Description

- Figures 1 to 3 show a first element (panel 10) being maintained in a spatial relationship with a second element (tubular steel frame 12). Figure 1 shows
15 fastener insert 14 inserted in an opening 16 provided for the purpose in tubular steel frame 12. As can be seen from Figure 2, fastener insert 14 together with adjustable capsule 18 make up the second fastening means. The first fastening means comprises panel fastener 20 which is shown in Figure 2 attached (for example, by glue) to panel 10.

- 20 As can be seen from Figure 3, after adjustable capsule 18 is adjusted in the desired way within fastener insert 14, panel fastener 20 can be attached to adjustable capsule 18 and locked in place by locking pin 22.

- Adjustable capsule 18 is shown in more detail in Figures 4 to 8, while panel fastener 20 is shown in close-up view in Figure 9. As can be seen from Figures 4
25 and 5, adjustable capsule 18 has a series of serrations 24 and a locking rim 26 and includes keeper 28.

Figure 8 is a cross-sectional view taken along the lines 8-8 of Figure 4, while Figure 7 is a cross-sectional view taken along the lines 7-7 of Figure 5. As well as

keeper 28, the adjustable capsule 18 includes keeper 30. Locking pin 22 is shown located in the region of keeper 28.

A top view of adjustable capsule 18, as shown in Figure 5, can be seen in Figure 6.

With reference to Figure 8, walls 32 of adjustable capsule 18 are capable of flexing
5 inwardly where not prevented by locking pin 22.

Panel fastener 20, shown in Figure 9, includes ridged cylindrical wall 34 and a further keeper 36.

To operate this first embodiment, fastener insert 14 is positioned within tubular steel frame 12, preferably by adhesion. Adjustable capsule 18 is placed within
10 fastener insert 14, with locking pin 22 in the position shown in Figure 2. Panel fastener 20 is attached to panel 10, once again, preferably by adhesion. Adjustable capsule 18 is adjusted with reference to fastener insert 14 so that, when panel fastener 20 is attached, panel 10 will be at the required distance from tubular steel frame 12. Panel fastener 20 is then attached to adjustable capsule 18 by a push fit,
15 rigid cylindrical wall 34 causing flexible wall 32 to flex inwardly so that locking rim 26 is located in notch 38 (see Figure 9) of panel fastener 20. Locking pin 22 is caused to move upwardly until it contacts keeper 36 as shown in Figure 3. In this position, locking pin 22 maintains locking rim 26 in notch 38 and effectively locks panel fastener 20 to adjustable capsule 18, thus also maintaining panel 10 in the
20 desired relationship to tubular steel frame 12. Locking pin 22 can be caused to move by any desired means, preferably remote, such as by use of a radio, magnetic or electronic signal or in any other suitable manner, such as is described in international patent application No. PCT/AU99/00185.

Referring now to Figures 10 to 14, once again fastener insert 14 is shown inserted
25 in tubular steel frame 12 (Figure 10). Adjustable plate 40 having neck 42 is positioned within fastener insert 14. Locking pin 44 is at this stage in the unlocked position (refer Figures 11 and 12). Panel plate 46 having locking pins 48 is then inserted in position on adjustable plate 40, which is adjusted as to the correct height for the relationship between panel 10 and tubular steel frame 12 (Figure 12). Once
30 the correct height has been adjusted, adjustable plate 40 is locked into place within fastener insert 14 by causing locking pin 44 to abut keeper 50, as shown in Figure 13. Panel plate 46 is removed from adjustable plate 40, adhered to panel 12 and then reinserted in adjustable plate 40. If desired, locking pins 48 can be caused to lock panel plate 46 into position. As a further option, adhesive may now be
35 inserted generally between panel 10 and tubular steel frame 12. This is further

illustrated in Figures 15 and 16, which are a longitudinal cross-section taken at right angles to the views in Figures 10 to 14.

Figure 14 shows in close-up view fastener insert 14, adjustable plate 40 and panel plate 46. As is the case in the first embodiment (for example in Figure 1), fastener insert 14 includes internal serrations 52. Channel 54 is for location of tubular steel frame 12. Adjustable plate 40 has serrations 24 complementing internal serrations 52 on fastener insert 14. Keeper 50 maintains the legs of neck 42 in position. Adjustable plate 40 also includes resilient legs 56 and spacing legs 58. Resilient legs 56 are designed to lock legs 60 on panel plate 46 in channels 62. Panel plate 46, which is attached by adhesive 64 to panel 10 in Figure 13, includes locking pins 48 having keepers 66 and 68. Adjustable plate 40 is locked to tubular steel frame 12 by causing locking pin 44 to travel downwardly to abut keeper 50, as shown in Figure 13. Panel plate 46 is locked to adjustable plate 40 by causing locking pins 48 to move downwardly from the position shown in Figure 11 to that in Figure 12, for example. As before, the locking of locking pins 44 and 48 is optionally reversible by use of remote activation means.

As seen from Figures 15 and 16, a large quantity of adhesive 70 can be deposited on tubular steel frame 12 after panel plate 46 is unlocked from adjustable plate 40 for this purpose. Panel plate 46 is then locked into position in adjustable plate 40 to maintain the desired spatial relationship between panel 10 and tubular steel frame 12 while adhesive 70 cures (refer Figure 16).

A top view of the second embodiment is shown in Figure 17 and a side elevation in Figure 18.

The third embodiment is shown in Figures 19 to 28. This embodiment is similar to the previous embodiment and like parts will be labelled with like numbers.

However, whereas the previous embodiment showed a double fastener via locking pins 48 in panel plate 46, the present embodiment has a single fastener with two locking pins.

As before, fastener insert 14 is positioned within tubular steel frame 12 as in Figure 19 and neck 42 is adjusted in position using locking pin 44. After panel 10 has been adhered to panel fastener 72, panel 10 is checked for correct positioning in relation to tubular steel frame 12, as in Figure 21. Panel fastener 72 is then released from adjustable plate 40, as in Figure 22 and Figure 25. Adhesive 70 is deposited on tubular steel frame 12 and panel 10 and panel fastener 72 replaced and locked into position as shown in Figure 26.

Figure 27 shows this embodiment in top view and Figure 28 shows it in side elevation. It will be appreciated that Figure 26 is a longitudinal sectional view taken along the lines A-A of Figure 27, while Figure 23 is a cross-sectional view taken along the lines B-B of Figure 28.

- 5 The detail of this embodiment can be seen from Figure 24, which includes keepers 74, 76 and 78 as well as locking pins 80.

It will be appreciated by one skilled in the art that various changes may be made to the embodiments described and that other modifications may be effected without departing from the spirit and scope of the invention. For example, it is within the
10 scope of the invention to have the adjustment means on the fastening means attached to the panel rather than to the tubular steel frame, as illustrated. It is also within the scope of the invention to have adjustment means on both fastening means.

Industrial Applicability

- 15 The invention represents an important advance in jigging arrangements and is capable of making assembly line production far more accurate and efficient, while at the same time greatly reducing costs.

CLAIMS

1. A jiggling device for maintaining a first element in spatial relationship to a second element, the device including a first fastening means for connection to the first element and a second fastening means for connection to the second
5 element, at least one of the first and second fastening means including adjustment means for adjusting the spatial relationship between the first and second elements, the device also including locking means adapted to lock the first fastening means to the second fastening means.
2. A jiggling device as claimed in claim 1, wherein the first element is a panel for a
10 vehicle and the second element is part of a tubular frame therefor.
3. A jiggling device as claimed in claim 2, wherein the adjustment means is adapted to adjust the panel closer to or further away from the frame.
4. A jiggling device as claimed in claim 2 or 3, wherein the adjustment means is adapted to adjust the panel so as to be closer to or further away from an
15 adjacent panel.
5. A jiggling device as claimed in any one of claims 1 to 4, wherein the first and second fastening means, the adjustment means and/or the locking means are adapted to be manipulated manually.
6. A jiggling device as claimed in any one of claims 1 to 4, wherein the locking
20 means is adapted to be activated so as to be locked or unlocked remotely.
7. A jiggling device as claimed in any one of claims 1 to 6, wherein the adjustment means is associated more with one fastening means than the other.
8. A jiggling device as claimed in any one of claims 1 to 6, which includes two adjustment means, a first adjustment means associated with the first fastening
25 means and a second adjustment means associated with the second fastening means.
9. A jiggling device as claimed in any one of claims 1 to 8, in which the fastening means is connected to the respective element by means chosen from the group consisting of: adhesive, a collar into which the fastening means is fitted,
30 double-sided tape of suitable peel strength and moulding or forming the fastening means in or on the element.

10. A jiggling device as claimed in any one of claims 1 to 9, in which the adjusting means includes a series of serrations or a screw thread, in each case adapted to be received in a complementary shape.
11. A jiggling device as claimed in any one of claims 1 to 9, in which the adjustment
5 means includes first and second parts, one being able to slide into the other to permit adjustment.
12. A jiggling device as claimed in any one of claims 1 to 11, which includes intelligent means adapted to enable automated adjustment of the first element relative to the second element.
- 10 13. A jiggling device as claimed in claim 12, in which the intelligent means is capable of sensing an undesirable gap and of automatically activating the adjustment means to close the gap so that it falls within a preset tolerance.
14. A method for maintaining a first element in spatial relationship to a second element, the method including the steps of:
 - 15 i) connecting a first fastening means to the first element;
 - ii) connecting a second fastening means to the second element;
 - iii) adjusting the spatial relationship of the first element to the second element via adjustment means; and
 - iv) locking the first fastening means to the second fastening means.
- 20 15. The jiggling method claimed in claim 14, which includes a further step of connecting the first element to the second element.
16. The jiggling method claimed in claim 15, wherein the first element is connected to the second element by adhesion or welding.
17. The jiggling method of claim 14, wherein steps (i) to (iii) are carried out in any
25 order .
18. The jiggling method of any one of claims 1 to 17, wherein the first element is a panel for a vehicle and the second element is part of a tubular frame therefor.

19. The jiggling method claimed in any one of claims 14 to 18, wherein the step of locking the first fastening means to the second fastening means is carried out remotely.
20. The jiggling method of any one of claims 14 to 19, wherein the step of adjusting
5 the spatial relationship of the first element to the second element via adjustment means is carried out automatically.
21. A jiggling method for maintaining a first element in spatial relationship to a second element, substantially as described, with reference to Figures 1 to 9 or 10 to 18 or 19 to 28 of the accompanying drawings.
- 10 22. A jiggling device substantially as herein described with reference to any one of Figures 1 to 9 or 10 to 18 or 19 to 28 of the accompanying drawings.




FIGURE 1



FIGURE 2




FIGURE 3

FIGURE 6





FIGURE 7




FIGURE 8




FIGURE 5




FIGURE 4




FIGURE 9

FIGURE 11




FIGURE 10





FIGURE 12




FIGURE 13




FIGURE 14




FIGURE 15




FIGURE 16

FIGURE 17





FIGURE 18

FIGURE 19




FIGURE 20





FIGURE 21




FIGURE 22




FIGURE 23




FIGURE 24




FIGURE 25




FIGURE 26

FIGURE 27





FIGURE 28

INTERNATIONAL SEARCH REPORT

International application No.
PCT/AU02/00322

A. CLASSIFICATION OF SUBJECT MATTER		
Int. Cl. ⁷ : B62D 65/02, F16B 5/06		
According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED		
Minimum documentation searched (classification system followed by classification symbols)		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched AU: IPC B62D 65/02, F16B 5/06		
Electronic data base consulted during the international search (name of data base and, where practicable, search terms used) DWPI: Keywords: (JIG OR FIXTURE) AND (ADJUST OR ALIGN) AND (LOCK OR LATCH)		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	Derwent Abstract Accession No. 98-015591/02, Class Q43, JP 09279737 A (SEKISUI HOUSE KK) 28 October 1997	1-22
X	US 4826345 A (SALICE) 2 May 1989 Whole document	1-22
X	US 4340100 A (ANDERSON) 20 July 1982 Whole document	1-22
<input checked="" type="checkbox"/> Further documents are listed in the continuation of Box C <input checked="" type="checkbox"/> See patent family annex		
<p>* Special categories of cited documents:</p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier application or patent but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</p> <p>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art</p> <p>"&" document member of the same patent family</p>		
Date of the actual completion of the international search 10 May 2002		Date of mailing of the international search report 21 MAY 2002
Name and mailing address of the ISA/AU AUSTRALIAN PATENT OFFICE PO BOX 200, WODEN ACT 2606, AUSTRALIA E-mail address: pct@ipaustalia.gov.au Facsimile No. (02) 6285 3929		Authorized officer LIONEL BOPAGE Telephone No : (02) 6283 2153

INTERNATIONAL SEARCH REPORT

International application No.

PCT/AU02/00322

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	AU 46835/79 A (DEUTSCHER W.A. PTY. LTD.) 15 November 1979 Page 3 line 7 to page 9 line 29, claims 1-8 and figures 1-7	1-22
X	AU 87572/75 A (MONIER COLOURTILE PTY. LTD.) 15 December 1975 Page 1 line 15 to page 6 line 17, claims 1-9 and figures 1-5	1-22

INTERNATIONAL SEARCH REPORT
Information on patent family members

International application No.
PCT/AU02/00322

This Annex lists the known "A" publication level patent family members relating to the patent documents cited in the above-mentioned international search report. The Australian Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent Document Cited in Search Report		Patent Family Member					
US	4826345	EP	272519	JP	63318308		
							END OF ANNEX